



TAKE 5 OIL CHANGE / DRIVEN BRANDS CHARLOTTE NC

NA STA

| PART # PART | PART |

EQUIPMENT LIST, NOTES AND ADDITIONAL INFORMATION

The waste oil pump shall be a Samson Item # 2836 40gal/minute Aluminum 1" diaphragm pump; wall mount available from Samson, as well as filter/regulator and Y-Strainer or appropriate 1" filter and connection fittings.

The front of the rolling pan has a 3/4" galvanized plug that must be installed by equipment installers. On the rear of the pan is a 3/4" ball valve with the valve facing towards fine floor the employees can push it open with their toes. Threaded into the ball valve is a 3/4" gasoline swivel, or a 2-plane swivel. Threaded into the swivel is either a 3/4" bath filling, or a Push-Lok bath fitting. Either will work. Pushed onto the hose barb is 3/4" gasoline hose. It does not have to be too flexible. I wire is sufficient. Use worm gear hose clamps yeare applicable.

For a 3 bay, use approximately 75' of hose. The method of install is as follows:

- 1. Pull hose through 3" chase beginning in tank room. Pull all the way through to bay 3 and hook up to the rolling pan as described a
- 2. At the back of bay 2, cut the hose on the same side as the deep side of the rolling pans. Insert a galvanized tee or brass tee and install a large between the sea on the pan. Same thing on bay 1.
- 3. Cut and fit hose to Y-Strainer via reducer coupling from 1" to 3/4" and a hose barb. Use short pieces of 1" and an elbow to go to the inflationump. 9 Met is a 1" hose that is fitted to the top of the tank.
- 4. Used oil tanks are "bunged together" at the bottom with hoses and ball valves so all can be filled at once, and you are shut them off pempty them via pump truck through the fill cap.
- 5. It is recommended that an overfill alarm/air switch is used. Use the correct one for the date and part number of put anstalled. The alarm/switch will shut off the air to the pump at a certain fill level, preventing a spill.

The air compressor "Bel Aire, Item # 6061V". 2hp roll around compressor

The pit magnets are Item # 07661, a 24 inch black powder coated tool holds with yellow stripe. The Jam be Garlet Master Magnets at 800-525-3536 and the website is www.Magnetsource.com

-6'	,
72° D D D D D D D D D D D D D D D D D D D	
ELEVATION ANGLE REF. TO: STANDARD TANK DATE: 05/2008 SKE BY AV ULD Underwriters ULD Underwriters ULD Underwriters 1 - (A) 2" HPT FLANE C - (C) 3" HPT HLANE 0 - (D) 2" LEVENT HLANE BOOK DATE 1 - (D) 4" EVENT HLANE BOOK ULD ULT BOOK ULT BOO	MEP. STO 32-3; DE B. OF POUCK; DF TOKES B. OS SE SE D. APPROVAL:

CENTRAL Council Pricamasis			
CENTRAL Francisco de la companion consultar de construcción conferencias	eto or hy inchallence for some contribution on the contribution of	on Adel Con in Line Magnesian	
r franciscosos	uk may from 17 00 1 00 00 north de gar de grande for austrana Brown parts a		
Specifications			
Social	(A.n. Ak turc Piter Septime ville Gauge		
900	86238		
Assert!	Central Processée	V)	
Nakay passas (pa)	35046-25088	440	
Straying Seeker	6996		
\$9000.	0406		
Thread elec	7836-589		
Constant	00.00 to 100.000		

TAK

RESTRICT

REAL TO TO THE WORTH AVENUE

CINKLOTE AND THE AVENUE

SEFFEN

FIGURE OFFEN

FIGURE OF

1019 - 10:04em

06-24-2019

SHEET NAME
PLUMBING
DETAILS
SHEET NUMBER